

UV-resistant Acrylic Globe

Marine Grade stainless steel latches

Safety bond slots where required

DEC User Interface

Washable Exhaust Filters both sides (exhaust protection by internal positive pressure 24/7)

Hydrophobic HEPA Inlet Filter

Power and Data Conduit Entries, 3/4" US, PG21 Int.

Fix to structure using 4 M12 (1/2") stainless steel bolts (not supplied)

[460]  
R18.10

[885]  
34.85


[813]  
Ø 32.00

[724]  
28.50

[412]  
16.23

UNLESS OTHERWISE SPECIFIED:  
DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL ±  
ANGULAR: MACH ± BEND ±  
TWO PLACE DECIMAL ±  
THREE PLACE DECIMAL ±  
INTERPRET GEOMETRIC TOLERANCING PER:  
MATERIAL  
Aluminum & Stainless Steel  
FINISH  
Powder Coat RAL 9003 White Gloss  
DO NOT SCALE DRAWING

	NAME	DATE
DRAWN	TB	5/26/2016
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		



**TEMPEST**  
lighting inc.

TITLE:  
**Tornado Marine 2300 Lighting Enclosure**

SIZE <b>B</b>	DWG. NO. <b>2300.xxM</b>	REV <b>01</b>
------------------	-----------------------------	------------------

SCALE: 1:20 SHEET 1 OF 1