



[559]
22.00

[51]
1.99

Optional Vibration Mounts

[872]
34.35

[85]
3.36

[255]
10.03

[85]
3.36

[340]
13.39

[514]
20.24

[359]
14.12

[447]
17.60

Mounting Points,
with Vibration
Mounts

Ø0.38 [10] THRU

0.47 [12] X 0.86 [22]

Mounting Points,
without Vibration
Mounts

Wiring Connections

Line Set Connections

Back
Min. Clearance
300mm/12in

Left
Min. Clearance
300mm/12in

Right
Min. Clearance
600mm/24in

Front
Do not Obstruct

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±
ANGULAR: MACH ± BEND ±
TWO PLACE DECIMAL ±
THREE PLACE DECIMAL ±
INTERPRET GEOMETRIC
TOLERANCING PER:

MATERIAL

FINISH

DO NOT SCALE DRAWING

	NAME	DATE
DRAWN	TB	6/22/2022
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		



TITLE:
Oasis Outdoor Unit, 12k
BTU/hr

SIZE B	DWG. NO. 59.ODU.12	REV 01
------------------	-----------------------	-----------

SCALE: 1:20 SHEET 1 OF 1