



Optional Vibration Mounts

Ø0.38 [10] THRU

Mounting Points, with Vibration Mounts

[85]
3.36

[585]
23.02

[85]
3.36

[400]
15.75

0.50 [13] X 1.00 [25]

Mounting Points, without Vibration Mounts

[400]
15.75

[670]
26.38

Wiring Connections

Line Set Connections

Back
Min. Clearance
300mm/12in

Left
Min. Clearance
300mm/12in

Right
Min. Clearance
600mm/24in

Front
Do not Obstruct

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±
ANGULAR: MACH ± BEND ±
TWO PLACE DECIMAL ±
THREE PLACE DECIMAL ±
INTERPRET GEOMETRIC
TOLERANCING PER:
MATERIAL
FINISH
DO NOT SCALE DRAWING

| | NAME | DATE |
|-----------|------|-----------|
| DRAWN | TB | 6/22/2022 |
| CHECKED | | |
| ENG APPR. | | |
| MFG APPR. | | |
| Q.A. | | |
| COMMENTS: | | |



TITLE:
Oasis Outdoor Unit, 4-Zone, 48k BTU/hr

| SIZE | DWG. NO. | REV |
|-------------|----------------------|--------------|
| B | 59.ODU.MZ4/48 | 01 |
| SCALE: 1:20 | | SHEET 1 OF 1 |