

Tacit Configurator


Please complete this form and email to us at info@tempest.biz

Name						
Company						
Email						
Phone						
Projector & Lens Model #	Projector:	Lens:				
Tacit Model	56					
Quantity						
Destination Country						
Install Date						
Enclosure Type	Landscape □ Portrait □					
	Ultra Short Throw □					
Projector Slide	Left (as shown here) □ Right □					
	Front (custom) □ Back (custom) □					
Projector Mount	Landscape/UST: Feet Down ☐ Feet Up ☐ Portrait: Feet Left ☐ Feet Right ☐					
Supply Voltage	230VAC (L, N, E) □ 200-208VAC (L1, L2, E) □ (+ Neutral if desired for 120V aux power) 120VAC (L, N, E) □ (Tacit 050-204 only)					
Unistrut Kit	Yes, Qty No	Mounting: Top □ □ Bottom □				
Ethernet	Yes, Qty No	51.D4.23 (TSM) □ □ 51.D4.15 (TEMP) □				
Spare Inlet Filter	Yes, Qty No					
Color	Standard, Warm White 🗆					
	Standard, Black 🗆					
	Custom, RAL #					
	Gloss Level *%					
	* Gloss levels higher than 30% may show					
	up weld marks. Tempest advises against high gloss finishes and accepts no liability					
	in this event.					

Projector Power Outlet IEC 60320 C19 20Amp					ıx Power):			
IEC 60309 30/32Amp								
NEMA L6-20			A L6-30		🗆			
UST Lens Configuration:								
- Configura	cioii.							
				No.				
90deg Up □	90de	g Down		Pe	riscopic A			
C				6				
90deg Right □	90	deg Left		Pe	riscopic B			
Straight, Vshift Down 🗆 Straight, Vshift Up 🗖								
Custom Requests:								
Factory Use Only:								
SO Number								
Date								
Electrical	IEC		NEMA					

User manuals, 2D and 3D CAD drawings at www.tempest.biz





©Tempest Lighting, Inc., July, 2023 In the interest of continuous product improvement, specifications are subject to change without notice



11845 Wicks Street, Sun Valley, CA 91352, USA www.tempest.biz info@tempest.biz t: +1 818 787 8984 f: +1 818 252 7101

