

Typhoon Configurator

Please complete this form and email to us at info@tempest.biz

Name *		
Company *		
Email *		
Phone		
Projector & Lens Make/Model #	Projector: *	Lens: *
Typhoon Model *	54.	Quantity
Destination Country *		
Required by (date) *		
Supply Voltage *		
Options		
Thermal Insulation	Qty	No
Grab Handles	Qty	No
Truss Kit	Qty	No
Positive Pressure	Qty	No
Cyclovator	Qty	No
Angle Mount Kit	Qty	No
Stacking Kit	Qty	No
Drop Arms Kit	Qty	No
Unistrut Kit	Qty	Mounting No
Ethernet Comms	Qty	Type No
Spare Inlet Filter	Qty	No
Projector Power Outlet <i>(all types include IEC 60320 C13 Aux Power):</i>		
Select Type:		
Custom:		
Color, standard	Light Bronze	Black White
Color, custom <i>Gloss levels higher than 30% may show up weld marks. Tempest accepts no responsibility in this event.</i>	Custom, RAL #	
	Gloss Level	%
	Salt Fog Primer:	Yes No

Signal Connectors:		
Connector Types <i>(up to six Neutrik D-style feedthroughs)</i>	Position: <i>(indicate type)</i>	Text Label <i>(12 characters Max)</i>
Types: A: Ethercon B: OpticalCon C: HDMI D: Displayport E: BNC F: XLR5M G: XLR5F H: 3.5mm Jack J: Blank K: DVI G: Other: LAYOUT 1 2 3 4 5 6 7 8 9 DVI1 DVI2	1	1
	2	2
	3	3
	4	4
	5	5
	6	6
	7	7
	8	8
	9	9
	DVI 1 DVI 2	

Custom Requests:

Factory Use Only:	SO #:	Date:
Electrical:	IEC NEMA	Wiring p:
Test:	Function	Projector
Hardware Kit:		

