

Typhoon Configurator

Please complete this form and email to us at info@tempest.biz

Name *		
Company *		
Email *		
Phone		
Projector & Lens Make/Model #	Projector: *	Lens: *
Typhoon Model *	54.	Quantity
Destination Country *		
Required by (date) *		
Supply Voltage *		
Options		
Thermal Insulation	Qty	
Grab Handles	Qty	
Truss Kit	Qty	
Positive Pressure	Qty	
Cyclovator	Qty	
Angle Mount Kit	Qty	
Stacking Kit	Qty	
Drop Arms Kit	Qty	
Unistrut Kit	Qty	Mounting
Ethernet Comms	Qty	Type
Spare Inlet Filter	Qty	

Projector Power Outlet (all types include IEC 60320 C13 Aux Power):

Select Type:

Custom:

Color, standard	Light Bronze	Black	White
Color, custom <i>Gloss levels higher than 30% may show up weld marks. Tempest accepts no responsibility in this event.</i>	Custom, RAL #	Gloss Level	%
	Salt Fog Primer:	Yes	No

Signal Connectors:		
Connector Types (up to six Neutrik D-style feedthroughs)	Position: (indicate type)	Text Label (12 characters Max)
Types: A: Ethercon B: OpticalCon C: HDMI D: Displayport E: BNC F: XLR5M G: XLR5F H: 3.5mm Jack J: Blank K: DVI G: Other: LAYOUT 1 2 3 4 5 6 7 8 9 DVI1 DVI2	1	1
	2	2
	3	3
	4	4
	5	5
	6	6
	7	7
	8	8
	9	9
	DVI 1	DVI 2

Inlet Power Connector(s). Select from US (N. America), INT (International)

Select Type:

Custom:

Custom Requests:

Factory Use Only:	SO #:	Date:
Electrical:	IEC	NEMA Wiring p:
Test:	Function	Projector
Hardware Kit:		